

Innlights

Displaysolutions

InnScreen D2 **5Gbit**

SHARP CORNER

[Pixel Pitch 2.6 mm]

// SUPER HIGH DEFINITION RENTAL / INDOOR

High-Definition. Ultra-Clear. Versatile.

Super-high resolution indoor rental panel with vivid, ultra-sharp image quality and flexible screen design.


The 90° corner panel of the D2-series enables advanced 3D setups with sharp corners.

- / Sharp corner / **90°**
- / Cuboid
- / Exceptional image experience
- / Super high refresh rate / **7680 Hz**
- / Super-high contrast ratio / **19500:1**
- / **5 Gbit bandwidth transmission**

D2-SERIES: FULLY CROSS-COMPATIBLE

- / D2 / Seamless flat 0° / $\pm 3^\circ$ / $\pm 6^\circ$
- / D2 ROUND CORNER / 160 mm radius
- / **D2 SHARP CORNER / 90°**

Supports
5G
INNVISION
VIDEO PROCESSING



Innlights

Displaysolutions

InnScreen D2 **SHARP CORNER** 5Gbit

PHYSICAL SPECS


Pixel Pitch [mm]	2,6
Brightness [cd/m²]	≥ 1.500
Weight [kg/m²]	32
Panel Size [mm]	500 × 500 × 71
Panel Resolution [px]	192 × 192
Pixel Density [px/m²]	147.456
Protection Level [Front/Back]	IP 20

VISUAL SPECS

Viewing Angle Hor/Ver [Deg]	160 / 140
Refresh Rate Min. [Hz]	7.680
Scan	1 / 16
IC Driver	MBI 5264
LED Type	Mini 4 in 1
Contrast Ratio	19.500
Grayscale Max. [bit]	22
Color depth [bit]	8 / 10 / 12
Dyn. Frame Frequency Max. [Hz]	240
Video Processing	INNVISION H5 <i>built on Colorlight</i>



360°
CUBE



INNLIGHTS STANDARDS

WEEE-Reg.-No.: DE 55860379
Certificates: TUV CE, EMC CE (EMV)

POWER

Voltage [V]	110 - 220
Power Cons. Max./Avg. [W/m²]	560 / 224

ENVIRONMENT

Operating Humidity [RH]	10% ~ 55%
Operating Temp. Min./Max. [°C]	-20 / +40