Innlights
Displaysolutions



NEW

Pop-Up Display **COB**

[Pixel Pitch 1.56 mm]

// PRO-GRADE / MODULAR / INDOOR

Vivid. Fine-Pitch. Modular.
COB LED technology with a 1.56 mm pixel pitch for sharp, high-impact visuals in a ready-to-use LED poster format.
Quick setup and easy repositioning. Used individually or seamlessly combined into larger screen formats. 180° fold for double-sided use and significantly reduced transport dimensions.
Fully integrated INNVISION Cloud for remote content publishing, display control and monitoring.

/ Exceptional fine-pitch visual performance
/ **COB** (Chip On Board) technology
/ Quick setup & repositioning
/ Seamless multi-display screens
/ Fully integrated INNVISION Cloud



Innlights
Displaysolutions

Pop-Up Display **COB**

PHYSICAL SPECS

Pixel Pitch [mm]	1.56
Protection Level [Front/Back]	IP65 / IP20
Total Weight [kg]	34
Screen Size [mm]	500 × 2000
Screen Resolution [px]	320 × 1280
Modules per Panel (W × H)	2 × 8
Panel Material	Die-cast aluminum

VISUAL SPECS

Brightness [cd/m²]	600
Viewing Angle H/V [°]	160 / 160
Refresh Rate Min. [Hz]	3840
IC	ICN1065
LED Type	COB
Grey Scale [bit]	14
Contrast Ratio	20000:1
Video Processing	INNVISION K10 *built on Colorlight*

180° FOLD
DOUBLE-SIDED SCREEN
COMPACT TRANSPORT



SEAMLESS
6× POP-UP DISPLAY
1920 × 1280 px



INNLIGHTS STANDARDS

WEEE-Reg.-No.: DE 55860379
Certificates: TUV CE, EMC CE (EMV)

POWER

Input Voltage [V AC]	100–240
Power Cons. Max./Avg. [W/m²]	300 / 100

ENVIRONMENT

Operating Humidity [RH]	10% ~ 80%
Operating Temp. Min./Max. [°C]	-20 / +50

All data without warranty.